

REMARKS

Applicants respectfully request that the above preliminary amendment be entered, and that the fees due herewith are calculated using the new claims, not the claims of the PCT application.

Respectfully submitted,



Eric J. Groen, Reg. No. 32,230
BAKER & DANIELS
205 West Jefferson Blvd., Suite 250
South Bend IN 46601
(219) 234-4149

185 Figs. 14 and 15 show a sectional side view and a top plan view, respectively, of a form chain having chain links according to Figs. 12 and 13.

190 Figs. 1 to 4 illustrate a first embodiment of the transport system according to the invention. The transport system consists of a form chain 1 (cf. Fig. 4) composed of a series of chain links 2. Each chain link 2 has an accommodation cavity 3 in which one small component 4
 195 each can be accommodated and fixed. For fixing the small components 4, the chain link has a rigid wall 5 and a resilient wall 6. The resilient wall 6 consists of an outer wall 7 having on the inside thereof a central web 8 extending in the direction of insertion of the small
 200 components 4 and having on both sides thereof resilient arms 9 extending therefrom. Between the free ends of the resilient arms 9 and the inside of the outer wall 7 there is thus formed an air gap 10 into which the resilient arms 9 can retract upon accommodation of a small
 205 component 4. The resilient arms ~~10~~⁹ on the outsides thereof, have a bead 11 facing in the direction of the accommodation cavity 3 and extending in the direction of insertion of the small components 4 on the resilient arms 9. By means of the beads 11 on the resilient arms
 210 9, the small component 4 thus is urged against the opposite rigid wall 5 and fixed. The resilient arms 9 as well as the beads 11 extend over the full height of the accommodation cavity so that the small component to be
 215 accommodated can be fixed at all levels. The accommodation cavity 3 is designed as through opening, permitting access to the component from both sides thereof.

On the outside of rigid wall 5, there are arranged two lateral arms 12 and 13 each having a bore 14 for accom-
 220 modating a pin for connecting the chain links. On the opposite side of chain link 2, the outside of outer wall

7 has a central arm 16 with a bore 17 arranged thereon which, upon connection of the chain links 2, is slid between the two lateral arms 12 and 13 and is connected thereto by insertion of the common pin 15. The width of the central arm 16 is matched to the spacing between the two lateral arms 12, 13 such that the chain links still can be pivoted well about the connecting pin 15, while however axial movement between the chain links is excluded. The resilient wall 6 and the rigid wall 5 in the embodiment shown are laterally connected via the two side walls 18 and 19. These side walls 18 and 19 are spaced apart exactly in the length of the component 4 to be accommodated. Rigid wall 5, along the majority of its length, has a U-spaced recess 20, so that the component to be accommodated is urged against the lateral sections 5a and 5b of wall 5 only.

On the outside of side walls 18 and 19, there are arranged elongate projections 21 and 22 in the longitudinal direction of the chain, which serve for guiding the chain links. These projections 21 and 22 are arranged at the same level as pins 15 mutually connecting the chain links, and in the width thereof approximately correspond to the diameter of the pins 15. The pins 15 project beyond the outsides of lateral arms 12, 13 to such an extent that the face side thereof is flush with the outside of projections 21, 22.

In an embodiment not shown in the drawings, there are provided no side walls 18, 19 and rigid wall 5 as well as resilient wall 6 are connected via the projections 21, 22 only.

The exact positioning of the chain links in the tool takes place by means of pins 15 that are made of metal. In contrast thereto, the remainder of the chain links is made by inexpensive plastics injection molding. Due to

260 guiding and positioning on the projecting sections of the metal pins 15, wear on the plastics body is avoided, and particle formation due to wear, involving great problems in the production of electronic components, is eliminated.

265 Fig. 4 illustrates a form chain in a top plan view, with the form chain consisting of chain links as described with reference to Figs. 1 to 3. This form chain 1 is a vertically deflectable form chain, i.e. the pins 15 are arranged perpendicularly to the direction of insertion
270 of the components 4 in the accommodation cavities 3.

Figs. 5 and 6 show a side view and a top plan view, respectively, of a chain link of a horizontal form chain. The essential difference from the chain links shown in
275 Figs. 1 to 4 resides in that the connecting pin 15 (shown in Fig. 5) extends in the direction of insertion of a component 4 in the accommodation cavity. The lateral arms 12, 13 thus are arranged above each other on rigid wall 5. The bore 17 in the central arm 16 arranged
280 on the opposite outer wall 7 also extends in the direction of insertion of a component in the accommodation cavity 3, so that the central arm 16, upon mating of chain links 2, can be received between the lateral arms 12, 13. In this embodiment, the pin 15 is not arranged
285 to be projecting beyond the lateral arms 12, 13, so that fixing of the chain links 2 in the tool takes place via the lateral projections 21 and 22 only. All other features are analogous to the chain link described in Figs. 1 to 4.

290

A horizontal form chain consisting of chain links as described in Figs. 5 and 6 can be bent in horizontal direction and thus may easily be passed to processing stations distributed in a room.

295

Figs. 7 to 11 shows the constituent parts of a form chain 1 with two pivot axles or pins 15a and 15b as well as part of the form chain proper. All features corresponding to the form chain according to Figs. 1 to 4 bear the same reference numerals and will not be described in the following. The form chain with two pivot pins consists of chain links 2 (cf. Figs. 7 and 8) and connecting pieces 23 (cf. Figs. 9 and 10) which are inserted between the chain links 2 upon assembly of the form chain. The chain links 2 on one side thereof receive the pin 15a transversely to the direction of insertion of the small components 4 in the accommodation cavity 3 and on the opposite side thereof receive the pin 15b perpendicularly to said direction of insertion of the small components 4 in the accommodation cavity. In the embodiment shown, the lateral arms 12a and 13a on the side of rigid wall 5 are arranged so as to receive pin 15a transversely to the direction of insertion in accommodation cavity 3, whereas on the side of resilient wall 6 on outer wall 7, the lateral arms 12b and 13b are arranged above each other so that they can receive the connecting pin 15b in the direction of insertion in the accommodation cavity. The connecting piece 23 shown in Figs. 9 and 10 consists of two halves 23a and 23b that are mutually identical, but connected to each other in a manner displaced by 90°. Each of the connecting halves 23a and 23b has a bore 24a and 24b, respectively, through which the pins 15a and 15b, respectively, are introduced upon assembly of the form chain.

325

In the embodiment shown, the lateral arms 12a and 13a are spaced apart by the same distance as lateral arms 12b and 13b. Due to this, the two halves 23a and 23b of the connecting piece can be formed in identical manner and just need to be offset from each other by 90°.

330

However, it is just as well possible to space the lateral arms 12a and 13a as shown in Fig. 2 and to form the connecting piece 23a correspondingly wider.

335

Fig. 11 shows the form chain with the chain links according to Figs. 7 and 8 and the connecting piece according to Figs. 9 and 10 in the assembled state. The half 23a of the connecting piece is received between lateral arms 12a and 13a, and the other half 23b is received between lateral arms 12b and 13b of the adjacent connecting piece. By insertion of the pins 15a and 15b, the chain links are fixedly connected to each other so as to be pivotable about pins 15a and 15b, respectively.

345

The pins 15a laterally project beyond the outsides of the lateral arms 12a and 13a to such an extent that the end faces are aligned with the outside of projections 21 and 22. This form chain, which is double-deflectable, thus may also be guided via the projections 21, 22 and the pins 15a.

350

Figs. 12 to 15 show an additional embodiment of a vertically deflectable form chain. Features corresponding to those of the form chains described hereinbefore bear the same reference numerals and shall not be elucidated in more detail. The chain links of this form chain, on the side of rigid wall 5, are provided as well with two lateral arms 12, 13 having respective bores 14. On the opposite side, the chain link has two additional lateral arms 25, 26 which, with respect to their position, are arranged internally of the lateral arms 12, 13 and have circular axle-type projections 27 on the outside thereof which upon mating of the chain links engage the bores 14 of lateral arms 12, 13 of the adjacent chain link from the inside thereof. The end faces of lateral arms 12, 13 are each formed with a slope 28 extending inwardly. Upon mating of the chain links, the slope 28 rides onto the

355

360

365

T05060 ESE45860

axle-type projections 27, whereby the lateral arms 12,
370 13 are resiliently bent outwardly and the axle-type pro-
jections 27 may latchingly engage the bores 14. In this
embodiment, the resilient wall 6 consists of two resil-
ient arms ~~28~~³¹ which at the lower end thereof are fixedly
connected to outer wall 7 and the upper end of which
375 urges the component 4 against the opposite rigid wall 5.
The resilient arms ~~28~~³¹ at the upper inside thereof, are
provided with a bead 29 exerting pressure on the outside
of the component 4.

380 For centering the chain link in a processing station,
the outside of stationary wall 5 is formed with a slope
30 at which the centering means of the tool engages,
thereby exactly determining the position of the chain
link in the tool.

385 The invention is not restricted to the embodiments
shown. For example, it is also possible to employ the
resilience feature depicted in the preceding embodiments
in the form chain according to Figs. 12 to 15.

390